

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 August 2003 (07.08.2003)

PCT

(10) International Publication Number
WO 03/065750 A1

(51) International Patent Classification⁷: **H04Q 7/38**

(21) International Application Number: **PCT/EP01/15345**

(22) International Filing Date:
27 December 2001 (27.12.2001)

(25) Filing Language: **English**

(26) Publication Language: **English**

(71) Applicant (for all designated States except US): **NOKIA CORPORATION [FI/FI];** Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MUHONEN, Ahti [FI/FI];** Holperintie 39, FIN-04680 Hirvihaara (FI). **STAACK, Jens [DE/FI];** Jättäläisenkaari 3 C 10, FIN-02400 Kirkkonummi (FI).

(74) Agent: **UNGERER, Olaf;** Eisenführ, Speiser & Partner, Association No. 15, Arnulfstr. 25, 80335 Munich (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **METHOD AND SYSTEM FOR LOCATING A MOBILE TERMINAL**



(57) Abstract: The present invention relates to a method and system for locating a mobile terminal addressed in a location service request by an overlay identity. A database (60) is accessed to obtain a first routing information of the mobile terminal based on the overlay identity, and the first routing information is then used to access a subscriber database (40) in order to derive a second routing information and a cellular identity of the mobile terminal (10), based on which a location service of the cellular network is initiated. Thereby, a LCS clients of the overlay system (e.g. IMS) can be supported in current LCS services to enhance their functionality.

WO 03/065750 A1

Method and system for locating a mobile terminal

5

FIELD OF THE INVENTION

The present invention relates to a method and system for locating a mobile terminal in a cellular network based on a request received from an overlay system,
10 such as a IP (Internet Protocol) Multimedia Subsystem (IMS).

BACKGROUND OF THE INVENTION

In general, overlay systems may be provided in cellular or fixed networks for enabling network operators to offer specific services based on and built upon applications, services and protocols not supported in their networks. The intention is that
15 such services will be developed by the network operators and other third party suppliers using the mechanisms provided by external networks, such as the Internet or other external network systems or subsystems.

20

Recently, an IP Multimedia core network Subsystem (IMS) has been developed which comprises all core network elements for provision of multimedia services. This includes a collection of signalling and bearer related network elements as defined e.g. in the Third Generation Partnership Project (3GPP) specification TS
25 23.002. IP Multimedia services are based on an IETF (Internet Engineering Task Force) defined session control capability which, along with multimedia bearers, utilizes the PS (Packet Switched) domain of the cellular network. In order to achieve access independence and to maintain a smooth operation with wireless terminals across the Internet, the IMS attempts to be conformant to IETF "Internet
30 Standards". Therefore, the interfaces specified conform as far as possible to these standards for the case where an IETF protocol has been selected, e.g. SIP (Session Initiation Protocol). The IMS enables the convergence of, and access to, voice, video, messaging, data and to web-based technologies for the wireless

- 2 -

user, and combines the growth of the Internet with the growth in mobile communications.

As already mentioned, the IMS utilizes the PS domain to transport multimedia signalling and bearer traffic. The PS domain maintains the service while the mobile terminal moves and hides these moves from the IMS. The IMS is independent of the CS (Circuit Switch) domain although some network elements may be common with the CS domain. This means that it is not necessary to deploy a CS domain in order to support an IMS based network. A User Equipment (UE) (or mobile station (MS)) consists of a mobile equipment (ME with a valid USIM (Universal Mobile Telecommunications System Subscriber Identity Module) (or SIM (Subscriber Identity Module)) attached. In the following, the abbreviation "UE" refers both to MS and user equipment, even those used for emergency calls, which do not have a valid SIM or USIM.

A UE accessing an IMS service requires an IP address which can be logically part of the visited network GPRS IP addressing domain. There are various identities which may be associated with a user of IP multimedia services. Every IMS subscriber has one or more public user identities. The public user identity is used by any user for requesting communications to other users. For example, this might be included on a business card. Both telecom numbering and Internet naming schemes can be used to address users depending on the public user identities allocated to the users. The public user identity may take the form of a SIP URL (Uniform Resource Locator) as defined in RFC 2543 and RFC 2396, or an E.164 number. At least one public user identity may be used to identify the user's information within a subscriber database, e.g. the Home Subscriber Server (HSS), e.g. during mobile terminated set-up.

A location service (LCS) feature in UMTS and GSM (Global System for Mobile Communications) provides a mechanism to support mobile location services for operators, subscribers and third party service providers. Location services may be considered as a network provided enabling technology consisting of standardized

- 3 -

service capabilities which enable the provision of location applications. The applications may be service provider specific. In general, LCS is a service concept in a system standardization. LCS specifies all necessary network elements and entities, their functionalities, interfaces as well as communication messages to implement the positioning functionality in a cellular network. Positioning is a functionality which detects a geographical location of e.g. a mobile terminal. Principles and/or algorithms on which the estimation of the geographical location is based may be e.g. AOA, TOA or TDOA. For example, the Global Positioning System (GPS) is based on TOA while OTDOA and E-TD (on GSM) are based on TDOA.

10

The positioning of the UE is a service provided by the access network. In particular, all access networks (e.g. UMTS Terrestrial Radio Access Network (UTRAN), GSM/EDGE (Enhanced Datarate for GSM Evolution) Radio Access Network (GERAN), which facilitate determination of the locations of UEs, shall be able to exchange location information with a core network as defined in the 3GPP specification TS23.271, when connected to a core network.

By making use of the radio signals, the capability to determine the (geographic) location of the UE can be provided. The location information may be requested by and reported to a client (application) associated UE or by a client within or attached to the core network. The location information may also be utilized internally in a system, for example, for location assisted handover or to support other features, such as home location billing. The position information may be reported in standard, e.g. geographical coordinates, together with the time-of-day and the estimated errors (uncertainty) of the location of the UE according to the 3GPP specification TS 23.032. There are many different possible uses for the location information. As already mentioned, the positioning feature may be used internally by the GSM/UMTS network (or attached networks), by value-added network services, by the UE itself or through the network and by the third parties' services. The positioning feature may also be used by an emergency service. Although LCS has been defined for the CS and PS domains of cellular networks, it has not yet been

30

- 4 -

defined for the IMS domain. Currently, the LCS service does not support IMS LCS clients to be addressed by IMS identities.

SUMMARY OF THE INVENTION

5

It is therefore an object of the present invention to provide a method and system for locating a mobile terminal addressed by an overlay identity used in an overlay system, e.g. an IMS identity used in the IMS.

- 10 This object is achieved by a method of locating a mobile terminal in a cellular network, said method comprising the steps of:
- receiving a location service request including an overlay identity of an overlay system;
 - accessing a database storing a first routing information of said mobile terminal
 - 15 based on said overlay identity;
 - Using said first routing information to access a subscriber database in order to derive a second routing information and a cellular identity of said mobile terminal;
 - and
 - initiating a location service of said cellular network based on said derived second
 - 20 routing information and cellular identity.

- Additionally, the above object is achieved by a system for locating a mobile terminal in a cellular network, said system comprising:
- a gateway node for receiving a location service request including an overlay identity of said mobile terminal in an overlay system;
 - 25 a database storing a first routing information of said mobile terminal;
 - wherein said gateway node is arranged to access said database based on said overlay identity, to use said first routing information for an access to a subscriber database in order to derive a second routing information and a cellular identity,
 - 30 and to initiate a location service of said cellular network based on said derived second routing information and cellular identity.

- 5 -

Furthermore, the above object is achieved by a gateway node for initiating a location service for locating a mobile terminal in a cellular network, said gateway node being arranged to read a first routing information from a database based on a received overlay identity of said mobile terminal in an overlay system, to use said
5 first routing information for an access to a subscriber database in order to derive a second routing information and a cellular identity, and to perform said initiation based on said derived second routing information and cellular identity.

Accordingly, an address mapping functionality is provided for enabling a location
10 service for clients in overlay systems to be addressed by overlay identities, using existing LCS functionalities.

Preferably, other identities of said mobile terminal may be derived from said subscriber data base in said subscriber data base access step. In particular, the other
15 identities may be stored in a network element having a mobile location function. Thereby, signaling requirements for deriving the other identities of the mobile terminal in future location service requests can be reduced significantly. The overlay identity may be an IMS identity, in particular a SIP URL.

20 Furthermore, the first routing information may be a country code, e.g. a Mobile Country Code (MCC), and a network code, e.g. Mobile Network Code (MNC), of said mobile terminal.

The subscriber database access step may preferably be performed by using a
25 MAP query, such as a MAP-SEND-ROUTING-INFO-FOR-LCS service function.

The cellular identity may be an MSISDN or IMSI, and the second routing information may be an address of a network element having a switching function in the cellular network.

30 The gateway node may be a Gateway Mobile Location Center (GMLC). The database may be comprised in the gateway node or may be a separate external entity.

- 6 -

The subscriber database may be a Home Location Register (HLR) of the cellular network. In this case, the HLR may be arranged to derive the second routing information and the cellular identity by performing a query to a Home Subscriber Server. Furthermore, the HLR may be arranged to derive other identities of the terminal device.

Preferably, the database may be arranged to provide a mapping function between the first routing function and the overlay identity of the terminal device.

Furthermore, the gateway node may be arranged to store the second routing information and/or the cellular identity, for further use.

BRIEF DESCRIPTION OF THE DRAWINGS

In the following, the present invention will be described in greater detail based on a preferred embodiment with reference to the accompanying drawings, in which:

Fig. 1 shows a network architecture for implementing a location service function according to the preferred embodiment of the present invention;

20

Fig. 2 shows a signaling diagram indicating exchanged signaling messages and procedures in a location service function according to the preferred embodiment of the present invention; and

Fig. 3 shows a table indicating parameters of a MAP query function used in the preferred embodiment;

DESCRIPTION OF THE PREFERRED EMBODIMENT

The preferred embodiment will now be described based on an LCS architecture in a UMTS network as shown in Fig. 1. According to Fig. 1, a reference point, called Le Interface, is shown between an LCS server (here: GMLC 50) and an LCS client 80 which, in the present embodiment, is an IMS server or application. The Le ref-

- 7 -

erence point is described in the 3GPP Specification TS 22.071. However, there may be more than a single LCS network interface to several different LCS clients or other networks. These networks may both differ in ownership as well as in communications protocol. The network operator may define and negotiate inter-connection with each external LCS client or other network. In general, an interface differs from a reference point in that an interface is defined where specific LCS information is exchanged and needs to be fully recognized.

Furthermore, an interface called Lg is arranged to connect two independent LCS networks, e.g. different PLMNs (Public Land Mobile Networks) for message exchange. The LCS functional entities are grouped into an LCS client functional group and an LCS server functional group. The LCS server functional group consists of functions in the UMTS PLMN supporting LCS, e.g. a client handling component, a system handling component, a subscriber handling component, and a positioning component. The LCS client 80 contains an LCS component with one or more clients, which by using location information can provide location based services. In particular, the LCS client 80 is a logical functional entity that requests from the LCS server in the PLMN location information for one or more than one target UE, i.e. a UE 10 shown in Fig. 1, within a specified set of parameters such as Quality of Service of QoS.

In the present architecture shown in Fig. 1, the LCS client 80 resides in an external entity belonging to an overlay system, i.e. the IMS. Via a location service request, the LCS client 80 communicates with the LCS server, i.e. GMLC 50, to request for the location information of the UE 10. Attributes identified by the location service request may be target UE, LCS identity, state, event, requested QoS information, local coordinate reference system, and/or geographical area. A location service response is sent to the LCS client 80 as the result of the location service request issued by the LCS server. Attributes identified for the location service response may be the location indication of the UE 10 in geographical coordinates, the location of the UE 10 as an ellipsoid with axes and direction of all axes, an estimated

- 8 -

achieved QoS, and/or an indication when UE 10 enters or leaves the geographical area.

Fig. 1 illustrates generally the relation of the LCS client 80 and servers in the core network with a GERAN 20 and a UTRAN 30. The LCS entities within the access networks communicate with the core network consisting of a 2G-MSC 22 of the CS domain, a 2G-SGSN 24 of the PS domain, a 3G-SGSN 32 of the PS domain, and an MSC server 34 of the PS domain across A, Gb and Iu interfaces. Communication among the access network LCS entities makes use of the messaging and signaling capabilities of the access network.

Furthermore, a subscriber database, i.e. a HLR/HSS 40 is provided for storing subscriber specific data of the UE 10 and other mobile terminals or equipments. It is noted that the HLR and HSS may be arranged at different locations, while the HLR part may include both 2G-HLR and 3G-HLR functionalities. In this respect it is noted, that the terms "2G" and "3G" denote second and third generation mobile communication functionalities, respectively.

With this configuration both the network and the UE 10 are able to measure the timing of signals and compute a location estimate of the UE 10. Depending on the applied positioning method it is possible to utilize the corresponding configuration containing all needed entities. For instance, if network-based positioning is applied, the entities that are involved in measuring the mobile's signal and calculating its location estimate are allocated to the network elements of the access stratum. On the other hand, in case mobile-based or network-assisted methods are used entities should be allocated to the UE 10.

The GMLC 50 contains functionality required to support LCS. In one PLMN, there may be more than one GMLC. The GMLC 50 is the first node the external LCS client 80 accesses in a GSM PLMN (i.e. the Lc reference point is supported by the GMLC 50). The GMLC 50 may request routing information from the HLR/HSS 40 via a Lh interface. After performing registration authorization, it sends positioning

- 9 -

requests to either the 2G-MSC 22, SGSNs 24, 32 or MSC server 34 and receives final location estimates from the corresponding entity via the Lg interface. The UE 10 may be involved in various positioning procedures. Specific UE involvement is specified in each of the positioning procedures mentioned in the 3 GPP specification TS 25305 for the UTRAN 30 and TS 43.059 for the GERAN 20. The 2G-MSC 22 contains a functionality responsible for UE subscription authorization and managing call related and non-call related positioning requests of LCS. The 2G-MSC 22 is accessible to the GMLC 50 via the Lg interface. The LCS functions of the 2G-MSC 22 are related to charging and billing LCS coordination, location request authorization and operation of the LCS services. If connected to the 2G-SGSN 24 through a Gs interface, it checks whether the UE 10 is GPRS attached to decide whether to page the UE 10 on the A or Gs interface.

The MSC server 34 handles the same functionality as the 2G-MSC 22 including charging and billing, LCS coordination, location requests, authorization and operation of the LCS services. The MSC server 34 is accessible to the GMLC 50 via the Lg interface. Furthermore, the 2G- and 3G-SGSNs 24, 32 contain a functionality responsible for UE subscription authorization and managing positioning requests of LCS. The SGSNs 24, 32 are accessible to the GMLC via the Lg interface. The LCS functions of the SGSNs 24, 32 are related to charging and billing, LCS coordination, location request, authorization and operation of the LCS services. The SGSNs 24, 32 forward the CS paging request received from the Gs interface to a base station subsystem or radio network controller of the respective access network.

The HLR/HSS 40 is accessible from the GMLC 50 via a Lh interface. For a roaming UE, the HLR/HSS 40 may be in a different PLMN.

Furthermore, a gsmSCF (GSM service control function) provides an Lc interface to support access between the LCS and a network functionality CAMEL (Customized Applications for Mobile Network Enhanced Logic) providing the mechanisms of

- 10 -

Intelligent Network to a mobile user. The procedures and signaling associated with it are defined in the 3GPP specification TS 23.078 and TS 29.002, respectively.

5 An important point is the possibility to address and indicate the target UE 10 using a cellular identity, e.g. the MSISDN (Mobile Station Integrated Services Data Network) or IMSI (International Mobile Subscriber Identity), or the like. However, in the present case, the external LCS client 80 belongs to the IMS and thus uses an IMS identity in the location service request supplied to the GMLC 50. Therefore, a mapping function is provided for mapping the IMS identity of the UE 10 with a routing information required for accessing the HLR/HSS 40 allocated to the target UE 10. Thereby, an IP addressing of the target UE 10 can be performed without requiring an active PDP context established between the target UE 10 and the external LCS client 80.

15 The Lh interface between the GMLC 50 and the HLR/HSS 40 may be based on a Mobile Application Part (MAP) protocol. This interface Lh is used by the GMLC 50 to request a routing information to the serving MSC or SGSN of the particular target UE 10 whose location has been requested. The Lg interface is used by the GMLC 50 to convey the location request to the respective MSC or SGSN function currently serving the target UE 10. Furthermore, the Lg interface is used by the 20 respective MSC or SGSN function to return location results to the GMLC 50.

For the LCS service, a MAP-SEND-ROUTING-INFO-FOR-LCS service is used between the GMLC 50 and the HLR/HSS 40 to retrieve the routing information 25 needed for routing a location service request to the serving MSC or SGSN function. In case the GMLC 50 receives a location service request from the external LCS client 80, which contains an IMS identity the GMLC 50 accesses the database 60 which may be arranged in the GMLC 50 or as a separate external entity to derive the routing information to the HLR/HSS 40. The IMS identity may be a public identity, such as a SIP URL, which is mapped by the HLR/HSS 40 to a cellular routing information, e.g. an MCC and MNC of the home network of the target 30 of the UE 10. Using this cellular routing information the GMLC 50 accesses the

- 11 -

HLR/HSS 40 by a MAP query, e.g. a MAP-SEND-ROUTING-INFO-FOR-LCS message comprising the IMS identity, e.g. SIP URL. The HRL part of the HRL/HSS 40 may access the HSS part based on an interworking function to obtain the IMSI or any other cellular identity of the target UE 10 from the HSS part
5 based on a corresponding mapping function. Using this cellular identity, the GMLC 50 initiates a location service function within the cellular network via the Lg interface. Thereby, an IMS LCS service functionality can be provided in the UMTS/GSM network architecture.

10 Fig. 2 shows a signaling diagram indicating basic signaling messages and procedures required for the location service function. In particular, the external LCS client 80 requests the current location of the target UE 10 from the GMLC 50 by using a LSC service request comprising the IMS ID of the target UE 10 (step 1). In response thereto, GMLC 50 accesses the database 60 and transfers the IMS ID to
15 the database 60. Based on the mapping function provided at the database 60 the corresponding cellular routing information MCC/MNC is returned to the GMLC 50. Then, the GMLC 50 uses this routing function to route a MAP query comprising the MS ID to the concerned HLR/HSS 40 identified by the MCC/MNC (step 2). In response thereto, the HLR/HSS 40 returns the cellular identity (e.g. MSI) of the
20 target UE 10 and a routing information (address of the serving network element) required for routing the LSC service request in the cellular network (step 3). Now that the GMLC 50 knows both, the IMSI and location of the serving network element, the location service procedure can be invoked in the cellular network (step 4). Finally, the GMLC 50 sends the location service response received from the
25 cellular network to the external LCS client 80 (step 5).

To implement the mapping function between the IMS identity and the cellular identity in the HLR/HSS 40, a new parameter has to be introduced into the MAP query message, e.g. the MAP-SEND-ROUTING-INFO-FOR-LCS message. Fig. 3 indicates this new parameter, e.g. IMS identity as a conditional parameter for location
30 service requests including an IMS identity. Thereby, the HLR/HSS 40 is in a position to provide the mapping function so as to retrieve the cellular identity of the

- 12 -

target UE 10. Thus, the MAP-SEND-ROUTING-INFO-FOR-LCS service is enhanced so that it can carry whatever public IMS identity is available to the GMLC 50. The GMLC 50 is arranged to put the IMS identity to the MAP-SEND-ROUTING-INFO-FOR-LCS service request message instead of the conventionally used cellular identity, e. g. IMSI or MSISDN. From the point of view of the HLR/HSS 40 the new parameter is optional, i.e. if provided, a query to the HSS part is needed to map the public IMS identity to the cellular identity. The HLR/HSS 40 then returns the retrieved cellular identity to the GMLC 50 in a MAP-SEND-ROUTING-INFO-FOR-LCS service reply and the conventional CS or PS LCS methods can be used to locate the UE 10. The GMLC 50 may store the mapping between the IMS identity and the cellular identity in its internal database or memory for further queries.

Furthermore, the preferred embodiment may be enhanced by returning all public IMS identities known in the HSS part of the HLR/HSS 40 to the GMLC 50, so that any further location requests with other identities would not require a HLR query at all as long as the location result in the GMLC 50 is still actual.

It is to be noted that the present invention is not restricted to the provision of a location service in a IMS environment, but can be used for providing a location service in any overlay system having an own overlay identity allocated to the target mobile terminal. Thus, the preferred embodiment may vary within the scope of the attached claims.

25

Claims

1. A method of locating a mobile terminal (10) in a cellular network, said
5 method comprising the steps of:
 - a) receiving a location service request including an overlay identity of an overlay system;
 - b) accessing a database (60) storing a first routing information of said mobile terminal (10) based on said overlay identity;
 - 10 c) using said first routing information to access a subscriber database (40) in order to derive a second routing information and a cellular identity of said mobile terminal (20); and
 - d) initiating a location service of said cellular network based on said derived second routing information and cellular identity.
- 15 2. A method according to claim 1, further comprising the steps of deriving other identities of said mobile terminal (10) from said subscriber database (40) in said step c).
- 20 3. A method according to claim 2, wherein said other identities are stored in a network element (50) having a mobile location function.
4. A method according to anyone of the preceding claims, wherein said overlay identity is IMS identity.
- 25 5. A method according to claim 4, wherein said IMS identity is a SIP URL.
6. A method according to anyone of the preceding claims, wherein said first routing information is a country code and a network code of said mobile
30 terminal (10).


- 14 -

7. A method according to anyone of the preceding claims, wherein said step c) is performed by using a MAP-SEND-ROUTING-INFO-FOR-LCS service function.
- 5 8. A method according to anyone of the preceding claims, wherein said cellular identity is an MSISDN or IMSI.
9. A method according to anyone of the preceding claims, wherein said second routing information is an address of a network element (22, 24, 32, 34),
10 having a switching function in said cellular network.
10. A system for locating a mobile terminal in a cellular network, said system comprising:
- 15 a) a gateway node (50) for receiving a location request including an overlay identity of said mobile terminal (10) in an overlay system; and
- b) a database (60) storing a first routing information of said mobile terminal;
- 20 c) wherein said gateway node (50) is arranged to access said database (60) based on said overlay identity, to use said first routing information for an access to a subscriber database (40) in order to derive a second routing information and a cellular identity,
- d) and to initiate a location service of said cellular network based on said derived second routing information and cellular identity.
- 25 11. A system according to claim 10, wherein said gateway node is a Gateway Mobile Location Center (50).
12. A system according to claim 10 or 11, wherein said database is comprised in said gateway node (50).
- 30 13. A system according to anyone of claims 10 to 12, wherein said subscriber database is a Home Location Register (40) of said cellular network.

- 15 -

14. A system according to claim 13, wherein said Home Location Register (40) is arranged to derive said second routing information and said cellular identity by performing a query to a Home Subscriber Server.
- 5
15. A system according to claim 13 or 14, wherein said Home Location Register (40) is arranged to derive other identities of said terminal device (10).
- 10
16. A system according to anyone of claims 10 to 15, wherein said database (60) is arranged to a mapping function between said first routing information and said overlay identity of said terminal device (10).
- 15
17. A system according to anyone of claims 10 to 16, wherein said gateway node (50) is arranged to store said second routing information and/or said cellular identity.
- 20
18. A gateway node for initiating a location service for locating a mobile terminal (10) in a cellular network, said gateway node (50) being arranged to read a first routing information from a database (60) based on a received overlay identity of said mobile terminal (10) in an overlay system, to use said first routing information for an access to a subscriber database (40) in order to derive a second routing information and a cellular identity and to perform said initiation based on said derived second routing information and cellular identity.

25

**Fig. 1**

2 / 2




Fig. 2

MAP-SEND-ROUTING-INFO-FOR-LCS

Parameter name	Request	Indication	Response	Confirm
Invoke Id	M	M(=)	M(=)	M(=)
MLC Number	M	M(=)		
MSISDN	C	C(=)	C	C(=)
IMSI	C	C(=)	C	C(=)
LMSI			C	C(=)
→ IMS Identity	C	C(=)	C	C(=)
Network Node Number			C	C(=)
GPRS Node Indicator			C	C(=)
Additional Number			C	C(=)
User error			C	C(=)
Provider error				O

Fig. 3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/15345

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 00 69199 A (NOKIA NETWORKS OY ;NAGHIAN SIAMA EK (FI)) 16 November 2000 (2000-11-16)	1,10,18
X	page 15, lines 23-34 page 16, line 7-25 page 31, lines 13-19; lines 19-21 page 31, line 26 - page 32, line 14 figure 5	1,10,18
X	page 16, line 17-14 page 31, line 14-19	2,3, 11-13,15
X	page 31, line 30	7,16,17
X	page 31, line 17	8
X	page 32, line 1-4	9
Y	page 15, line 23 -page 16, line 2	4-6
Y	page 15, line 23-25 page 16, line 24	14
	— -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

7 August 2002

Date of mailing of the international search report

16/08/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Mele, M

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 01/15345

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 01 91389 A (ERICSSON TELEFON AB L M) 29 November 2001 (2001-11-29)	4,5
Y	page 12, line 5 - line 16	4,5
Y	WO 01 72007 A (VILANDER HARRI TAPANI ;ERICSSON TELEFON AB L M (SE)) 27 September 2001 (2001-09-27)	5
Y	page 4, line 7-10 page 5, line 11 - line 25	5
Y	US 5 862 481 A (ISKRA SUSAN ET AL) 19 January 1999 (1999-01-19)	6
Y	column 4, line 46 - line 56	6
A	EP 1 158 826 A (NOKIA MOBILE PHONES LTD) 28 November 2001 (2001-11-28) the whole document	1,10,18
A	WO 01 99461 A (NOKIA NETWORKS OY ;MUHONEN JANNE (FI); DUFVA TATU (FI)) 27 December 2001 (2001-12-27) the whole document	1,10,18
Y	NAPOLITANO-RICAGNI: "UMTS all-IP Mobility Management, Call and session control Procedure" 24 March 2000 (2000-03-24), XP002149519 page 4; figure 1	14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/15345

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0069199	A	16-11-2000	WO 0069199 A1	16-11-2000
			AU 4037499 A	21-11-2000
			EP 1181836 A1	27-02-2002
			US 2002086682 A1	04-07-2002
WO 0191389	A	29-11-2001	US 2002036983 A1	28-03-2002
			AU 6094101 A	03-12-2001
			WO 0191389 A2	29-11-2001
WO 0172007	A	27-09-2001	AU 5217101 A	03-10-2001
			WO 0172007 A1	27-09-2001
US 5862481	A	19-01-1999	WO 9738544 A1	16-10-1997
EP 1158826	A	28-11-2001	FI 20001252 A	25-11-2001
			CN 1325242 A	05-12-2001
			EP 1158826 A2	28-11-2001
			JP 2002027516 A	25-01-2002
			US 2001055394 A1	27-12-2001
WO 0199461	A	27-12-2001	AU 7093101 A	02-01-2002
			WO 0199461 A1	27-12-2001